* PRODUCT INFORMATION *

HUSKEY [™] TF-1000 MULTI-PURPOSE PTFE GREASE

DESCRIPTION

HUSKEY TF-1000 GREASE is a versatile, multi-purpose grease containing powdered PTFE. It is blended from the highest quality selected oils and synthetic bases available. It is compounded by special processes and techniques to guarantee thorough dispersion and homogenization of the PTFE lubricating solids. A highly water resistant high temperature adhesive lubricant with the unique characteristics of PTFE. Rust and oxidation inhibiting characteristics are maximized to afford complete rust protection and long life of the lubricant.

USAGE

HUSKEY TF-1000 was especially designed to provide superior high-temperature performance. It was also engineered to afford excellent results in a wide variety of automotive, marine, household, agricultural, and industrial applications, such as: wheel bearings, ball joints, conveyors, universal joints, pilot bearings, electric motors and general plant lubrication; including all guide rails and sliding applications.

ADVANTAGES

- Plating Action is established between the metal-surfaces by the micron size self-lubricating PTFE that develops a smoother surface.
- Working life of both old and new parts is increased due to the PTFE filling in any metal imperfections.
- Friction is lowered, reducing contact and temperature, resulting in increased working life of the grease.
- Cost reduction is accomplished by increased parts life, less down-time and extended lubricating cycles.
- Light color base for use where positive evidence of lubrication depends on visual check or where cleanliness is preferred.

PACKAGING AVAILABILITY

Convenient disposable gun-loaded 14 oz. Cartridges, 1 gal. Pails, 5 gal. Pails, 15 gal. Kegs and 55 gal. Drums



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office: 1580 Industrial Avenue, Norco, California 92860 (951) 340-4000 · Fax: (951) 340-4011 (888) 4-HUSKEY · www.huskey.com Eastern Region Office: 8300 Corporate Park Drive, Macedonia, Ohio 44056 (330) 425-2567 · Fax: (330) 425-9637 (800) 238-LUBE

* PRODUCT INFORMATION

TYPICAL PROPERTIES

DESCRIPTION HUSKEY Product: TF-1000

Color: Cream

Base Oil: Semi-Synthetic
Thickener: Synthetic
Texture: Buttery
Base Solid Lubricant: PTFE

<u>TEST</u>	ASTM METHOD	RESULT
N.L.G.I. Grade		2
Worked Penetration, 60 strokes	D-217	265 - 295
Base Oil Viscosity, SUS @ 100°F SUS @ 210°F cSt @ 40°C cSt @ 100°C	D-445	700 76 135 14
Pour Point, °F	D-97	5
Flash Point, °F	D-92	525
Dropping Point, °F	D-566	NONE
Corrosion Preventative Test	D-1743	PASS
Timken OK Load, lbs.	D-2509	45

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION make no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation





HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office: 1580 Industrial Avenue, Norco, California 92860 (951) 340-4000 · Fax: (951) 340-4011 (888) 4-HUSKEY · www.huskey.com Eastern Region Office: 8300 Corporate Park Drive, Macedonia, Ohio 44056 (330) 425-2567 • Fax: (330) 425-9637 (800) 238-LUBE