


Piston Seals
Wipers
Compounds
Custom Parts
Specialty Parts
Services
Wear Guides
Rod Seals

QUALITY | VALUE | SERVICE

O-Rings



 **ALL SEALS**
THE SEALING SPECIALISTS



You need it now! We've got it.

Tired of hearing, "We can get it for you?" All Seals already got it in stock. That's crucial in today's marketplace where you have to seal the deal ASAP. You order, we ship. Same day.

We stock everything from the conventional to the unconventional. The AS568, "Aerospace Size Standard for O-Rings" is generally considered the U.S. size standard. No matter what you're looking for, you'll find it on the chart below. The one thing they all have in common is they're the industry's best.

Set your own standards – If the O-Ring you need simply doesn't exist, we'll create it for you. And if you need help in determining which size and material is perfect for your unique needs, our expert consultants are just a phone call away.

ALL COMPOUNDS BELOW ARE IN STOCK AND AVAILABLE FOR IMMEDIATE SHIPMENT.

O-RINGS

NITRILE (NBR)	OPERATING TEMPERATURE* -30° to +250° F	MATERIALS 70 durometer 90 durometer NSF*/FDA 70 durometer
VITON™ (FKM)	OPERATING TEMPERATURE* -15° to +400° F	MATERIALS Black 75 durometer Black 90 durometer Brown 75 durometer
ETHYLENE PROPYLENE (EPDM)	OPERATING TEMPERATURE* -60° to +250° F	MATERIALS 70 durometer 90 durometer NSF*/FDA 70 durometer
SILICONE (VMQ)	OPERATING TEMPERATURE* -65° to +400° F	MATERIALS 70 durometer
NEOPRENE (CR)	OPERATING TEMPERATURE* -40° to +225° F	MATERIALS 70 durometer
HYDROGENATED NITRILE (HNBR)	OPERATING TEMPERATURE* -25° to +300° F	MATERIALS Green 70 durometer
TEFLON® ENCAPSULATED SILICONE & VITON™	OPERATING TEMPERATURE* -75° to +400° F	MATERIALS Silicone core Viton™ Core
PTFE	OPERATING TEMPERATURE* -300° to +500° F	MATERIALS PTFE (55 shore D)

ALSO AVAILABLE UPON REQUEST:

Viton™: All types, Fluorosilicone, Perfluoroelastomer, Polyurethane, Butyl, UL compounds, NSF* compounds, Carboxylated Nitrile, PTFE coated, internally lubricated, colored compounds, metric and custom sizes.

*Operating ranges are approximate and apply to medium hardness (~70 Shore A) compounds. Harder or softer compounds will have different temperature ranges.

*NSF compounds are manufactured by RT Dygert.




Viton™ is a trademark of The Chemours Company FC, LLC.

QUATTRO SEALS™

NITRILE (NBR)	OPERATING TEMPERATURE* -30° to +250° F	MATERIALS 70 durometer
VITON™	OPERATING TEMPERATURE* -15° to +400° F	MATERIALS 75 durometer

BACKUP RINGS

HYTREL®	OPERATING TEMPERATURE* -40° to +250° F	MATERIALS Dynamic (55 shore D) Static (55 shore D)
NITRILE (NBR)	OPERATING TEMPERATURE* -30° to +250° F	MATERIALS Contoured 90 durometer
PTFE	OPERATING TEMPERATURE* -300° to +500° F	MATERIALS PTFE Split backup rings



Service? We run rings around the rest.

For over five decades, All Seals has been a world leader in servicing and supplying our customers with only the best quality O-Rings, Custom Molded Rubber Products, Seals and Machined Plastics at very competitive prices. We also offer time and money saving value added services like JIT/Kanban programs, pre-production and kitting, special marking and packaging options and more.

CROSS SECTION .070" ± .003"

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-001	.029	.004	.040	1/32	3/32	1/32
-002	.042	.004	.050	3/64	9/64	3/64
-003	.056	.004	.060	1/16	3/16	1/16
-004	.070	.005	.070	5/16	13/64	1/16
-005	.101	.005	.070	3/32	7/32	1/16
-006	.114	.005	.070	1/8	1/4	1/16
-007	.145	.005	.070	5/32	9/32	1/16
-008	.176	.005	.070	3/16	5/16	1/16
-009	.208	.005	.070	7/32	11/32	1/16
-010	.239	.005	.070	1/4	3/8	1/16
-011	.301	.005	.070	5/16	7/16	1/16
-012	.364	.005	.070	3/8	1/2	1/16
-013	.426	.005	.070	7/16	9/16	1/16
-014	.489	.005	.070	1/2	5/8	1/16
-015	.551	.007	.070	9/16	11/16	1/16
-016	.614	.009	.070	5/8	3/4	1/16
-017	.676	.009	.070	11/16	13/16	1/16

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-018	.739	.009	.070	3/4	7/8	1/16
-019	.801	.009	.070	13/16	15/16	1/16
-020	.864	.009	.070	7/8	1	1/16
-021	.926	.009	.070	15/16	1-1/16	1/16
-022	.989	.010	.070	1	1-1/8	1/16
-023	1.051	.010	.070	1-1/16	1-3/16	1/16
-024	1.114	.010	.070	1-1/8	1-1/4	1/16
-025	1.176	.011	.070	1-3/16	1-5/16	1/16
-026	1.239	.011	.070	1-1/4	1-3/8	1/16
-027	1.301	.011	.070	1-5/16	1-7/16	1/16
-028	1.364	.013	.070	1-3/8	1-1/2	1/16
-029	1.489	.013	.070	1-1/2	1-5/8	1/16
-030	1.614	.013	.070	1-5/8	1-3/4	1/16
-031	1.739	.015	.070	1-3/4	1-7/8	1/16
-032	1.864	.015	.070	1-7/8	2	1/16
-033	1.989	.018	.070	2	2-1/8	1/16
-034	2.114	.018	.070	2-1/8	2-1/4	1/16

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-035	2.239	.018	.070	2-1/4	2-3/8	1/16
-036	2.364	.018	.070	2-3/8	2-1/2	1/16
-037	2.489	.018	.070	2-1/2	2-5/8	1/16
-038	2.614	.020	.070	2-5/8	2-3/4	1/16
-039	2.739	.020	.070	2-3/4	2-7/8	1/16
-040	2.864	.020	.070	2-7/8	3	1/16
-041	2.989	.024	.070	3	3-1/8	1/16
-042	3.239	.024	.070	3-1/4	3-3/8	1/16
-043	3.489	.024	.070	3-1/2	3-5/8	1/16
-044	3.739	.027	.070	3-3/4	3-7/8	1/16
-045	3.989	.027	.070	4	4-1/8	1/16
-046	4.239	.030	.070	4-1/4	4-3/8	1/16
-047	4.489	.030	.070	4-1/2	4-5/8	1/16
-048	4.739	.030	.070	4-3/4	4-7/8	1/16
-049	4.989	.037	.070	5	5-1/8	1/16
-050	5.239	.037	.070	5-1/4	5-3/8	1/16

CROSS SECTION .103" ± .003"

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-102	.049	.005	.103	1/16	1/4	3/32
-103	.081	.005	.103	3/32	9/32	3/32
-104	.112	.005	.103	1/8	5/16	3/32
-105	.143	.005	.103	5/32	11/32	3/32
-106	.174	.005	.103	3/16	3/8	3/32
-107	.206	.005	.103	7/32	13/32	3/32
-108	.237	.005	.103	1/4	7/16	3/32
-109	.299	.005	.103	5/16	1/2	3/32
-110	.362	.005	.103	3/8	9/16	3/32
-111	.424	.005	.103	7/16	5/8	3/32
-112	.487	.005	.103	1/2	11/16	3/32
-113	.549	.007	.103	9/16	3/4	3/32
-114	.612	.009	.103	5/8	13/16	3/32
-115	.674	.009	.103	11/16	7/8	3/32
-116	.737	.009	.103	3/4	15/16	3/32
-117	.799	.010	.103	13/16	1	3/32
-118	.862	.010	.103	7/8	1-1/16	3/32
-119	.924	.010	.103	15/16	1-1/8	3/32
-120	.987	.010	.103	1	1-3/16	3/32
-121	1.049	.010	.103	1-1/16	1-1/4	3/32
-122	1.112	.010	.103	1-1/8	1-5/16	3/32
-123	1.174	.012	.103	1-3/16	1-3/8	3/32
-124	1.237	.012	.103	1-1/4	1-7/16	3/32
-125	1.299	.012	.103	1-5/16	1-1/2	3/32
-126	1.362	.012	.103	1-3/8	1-9/16	3/32
-127	1.424	.012	.103	1-7/16	1-5/8	3/32

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-128	1.487	.012	.103	1-1/2	1-11/16	3/32
-129	1.549	.015	.103	1-9/16	1-3/4	3/32
-130	1.612	.015	.103	1-5/8	1-13/16	3/32
-131	1.674	.015	.103	1-11/16	1-7/8	3/32
-132	1.737	.015	.103	1-3/4	1-15/16	3/32
-133	1.799	.015	.103	1-13/16	2	3/32
-134	1.862	.015	.103	1-7/8	2-1/16	3/32
-135	1.925	.017	.103	1-15/16	2-1/8	3/32
-136	1.987	.017	.103	2	2-3/16	3/32
-137	2.050	.017	.103	2-1/16	2-1/4	3/32
-138	2.112	.017	.103	2-1/8	2-5/16	3/32
-139	2.175	.017	.103	2-3/16	2-3/8	3/32
-140	2.237	.017	.103	2-1/4	2-7/16	3/32
-141	2.300	.020	.103	2-5/16	2-1/2	3/32
-142	2.362	.020	.103	2-3/8	2-9/16	3/32
-143	2.425	.020	.103	2-7/16	2-5/8	3/32
-144	2.487	.020	.103	2-1/2	2-11/16	3/32
-145	2.550	.020	.103	2-9/16	2-3/4	3/32
-146	2.612	.020	.103	2-5/8	2-13/16	3/32
-147	2.675	.022	.103	2-11/16	2-7/8	3/32
-148	2.737	.022	.103	2-3/4	2-15/16	3/32
-149	2.800	.022	.103	2-13/16	3	3/32
-150	2.862	.022	.103	2-7/8	3-1/16	3/32
-151	2.987	.024	.103	3	3-3/16	3/32
-152	3.237	.024	.103	3-1/4	3-7/16	3/32
-153	3.487	.024	.103	3-1/2	3-11/16	3/32

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-154	3.737	.028	.103	3-3/4	3-15/16	3/32
-155	3.987	.028	.103	4	4-3/16	3/32
-156	4.237	.030	.103	4-1/4	4-7/16	3/32
-157	4.487	.030	.103	4-1/2	4-11/16	3/32
-158	4.737	.030	.103	4-3/4	4-15/16	3/32
-159	4.987	.035	.103	5	5-3/16	3/32
-160	5.237	.035	.103	5-1/4	5-7/16	3/32
-161	5.487	.035	.103	5-1/2	5-11/16	3/32
-162	5.737	.035	.103	5-3/4	5-15/16	3/32
-163	5.987	.035	.103	6	6-3/16	3/32
-164	6.237	.040	.103	6-1/4	6-7/16	3/32
-165	6.487	.040	.103	6-1/2	6-11/16	3/32
-166	6.737	.040	.103	6-3/4	6-15/16	3/32
-167	6.987	.040	.103	7	7-3/16	3/32
-168	7.237	.045	.103	7-1/4	7-7/16	3/32
-169	7.487	.045	.103	7-1/2	7-11/16	3/32
-170	7.737	.045	.103	7-3/4	7-15/16	3/32
-171	7.987	.045	.103	8	8-3/16	3/32
-172	8.237	.050	.103	8-1/4	8-7/16	3/32
-173	8.487	.050	.103	8-1/2	8-11/16	3/32
-174	8.737	.050	.103	8-3/4	8-15/16	3/32
-175	8.987	.050	.103	9	9-3/16	3/32
-176	9.237	.055	.103	9-1/4	9-7/16	3/32
-177	9.487	.055	.103	9-1/2	9-11/16	3/32
-178	9.737	.055	.103	9-3/4	9-15/16	3/32

CROSS SECTION .139" ± .004"

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-201	.171	.005	.139	3/16	7/16	1/8
-202	.234	.005	.139	1/4	1/2	1/8
-203	.296	.005	.139	5/16	9/16	1/8
-204	.359	.005	.139	3/8	5/8	1/8
-205	.421	.005	.139	7/16	11/16	1/8
-206	.484	.005	.139	1/2	3/4	1/8
-207	.546	.007	.139	9/16	13/16	1/8
-208	.609	.009	.139	5/8	7/8	1/8
-209	.671	.009	.139	11/16	15/16	1/8
-210	.734	.010	.139	3/4	1	1/8
-211	.796	.010	.139	13/16	1-1/16	1/8
-212	.859	.010	.139	7/8	1-1/8	1/8
-213	.921	.010	.139	15/16	1-3/16	1/8
-214	.984	.010	.139	1	1-1/4	1/8
-215	1.046	.010	.139	1-1/16	1-5/16	1/8
-216	1.109	.012	.139	1-1/8	1-3/8	1/8
-217	1.171	.012	.139	1-3/16	1-7/16	1/8
-218	1.234	.012	.139	1-1/4	1-1/2	1/8
-219	1.296	.012	.139	1-5/16	1-9/16	1/8
-220	1.359	.012	.139	1-3/8	1-5/8	1/8
-221	1.421	.012	.139	1-7/16	1-11/16	1/8
-222	1.484	.015	.139	1-1/2	1-3/4	1/8
-223	1.609	.015	.139	1-5/8	1-7/8	1/8
-224	1.734	.015	.139	1-3/4	2	1/8
-225	1.859	.018	.139	1-7/8	2-1/8	1/8
-226	1.984	.018	.139	2	2-1/4	1/8
-227	2.109	.018	.139	2-1/8	2-3/8	1/8
-228	2.234	.020	.139	2-1/4	2-1/2	1/8

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-229	2.359	.020	.139	2-3/8	2-5/8	1/8
-230	2.484	.020	.139	2-1/2	2-3/4	1/8
-231	2.609	.020	.139	2-5/8	2-7/8	1/8
-232	2.734	.024	.139	2-3/4	3	1/8
-233	2.859	.024	.139	2-7/8	3-1/8	1/8
-234	2.984	.024	.139	3	3-1/4	1/8
-235	3.109	.024	.139	3-1/8	3-3/8	1/8
-236	3.234	.024	.139	3-1/4	3-1/2	1/8
-237	3.359	.024	.139	3-3/8	3-5/8	1/8
-238	3.484	.024	.139	3-1/2	3-3/4	1/8
-239	3.609	.028	.139	3-5/8	3-7/8	1/8
-240	3.734	.028	.139	3-3/4	4	1/8
-241	3.859	.028	.139	3-7/8	4-1/8	1/8
-242	3.984	.028	.139	4	4-1/4	1/8
-243	4.109	.028	.139	4-1/8	4-3/8	1/8
-244	4.234	.030	.139	4-1/4	4-1/2	1/8
-245	4.359	.030	.139	4-3/8	4-5/8	1/8
-246	4.484	.030	.139	4-1/2	4-3/4	1/8
-247	4.609	.030	.139	4-5/8	4-7/8	1/8
-248	4.734	.030	.139	4-3/4	5	1/8
-249	4.859	.035	.139	4-7/8	5-1/8	1/8
-250	4.984	.035	.139	5	5-1/4	1/8
-251	5.109	.035	.139	5-1/8	5-3/8	1/8
-252	5.234	.035	.139	5-1/4	5-1/2	1/8
-253	5.359	.035	.139	5-3/8	5-5/8	1/8
-254	5.484	.035	.139	5-1/2	5-3/4	1/8
-255	5.609	.035	.139	5-5/8	5-7/8	1/8
-256	5.734	.035	.139	5-3/4	6	1/8

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-257	5.859	.035	.139	5-7/8	6-1/8	1/8
-258	5.984	.035	.139	6	6-1/4	1/8
-259	6.234	.040	.139	6-1/4	6-1/2	1/8
-260	6.484	.040	.139	6-1/2	6-3/4	1/8
-261	6.734	.040	.139	6-3/4	7	1/8
-262	6.984	.040	.139	7	7-1/4	1/8
-263	7.234	.045	.139	7-1/4	7-1/2	1/8
-264	7.484	.045	.139	7-1/2	7-3/4	1/8
-265	7.734	.045	.139	7-3/4	8	1/8
-266	7.984	.045	.139	8	8-1/4	1/8
-267	8.234	.050	.139	8-1/4	8-1/2	1/8
-268	8.484	.050	.139	8-1/2	8-3/4	1/8
-269	8.734	.050	.139	8-3/4	9	1/8
-270	8.984	.050	.139	9	9-1/4	1/8
-271	9.234	.055	.139	9-1/4	9-1/2	1/8
-272	9.484	.055	.139	9-1/2	9-3/4	1/8
-273	9.734	.055	.139	9-3/4	10	1/8
-274	9.984	.055	.139	10	10-1/4	1/8
-275	10.484	.055	.139	10-1/2	10-3/4	1/8
-276	10.984	.065	.139	11	11-1/4	1/8
-277	11.484	.065	.139	11-1/2	11-3/4	1/8
-278	11.984	.065	.139	12	12-1/4	1/8
-279	12.984	.065	.139	13	13-1/4	1/8
-280	13.984	.065	.139	14	14-1/4	1/8
-281	14.984	.065	.139	15	15-1/4	1/8
-282	15.955	.075	.139	16	16-1/4	1/8
-283	16.955	.080	.139	17	17-1/4	1/8
-284	17.955	.085	.139	18	18-1/4	1/8

CROSS SECTION .210" ± .005"

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-309	.412	.005	.210	7/16	13/16	3/16
-310	.475	.005	.210	1/2	7/8	3/16
-311	.537	.007	.210	9/16	15/16	3/16
-312	.600	.009	.210	5/8	1	3/16
-313	.662	.009	.210	11/16	1-1/16	3/16
-314	.725	.010	.210	3/4	1-1/8	3/16
-315	.787	.010	.210	13/16	1-3/16	3/16
-316	.850	.010	.210	7/8	1-1/4	3/16
-317	.912	.010	.210	15/16	1-5/16	3/16
-318	.975	.010	.210	1	1-3/8	3/16
-319	1.037	.010	.210	1-1/16	1-7/16	3/16
-320	1.100	.012	.210	1-1/8	1-1/2	3/16
-321	1.162	.012	.210	1-3/16	1-9/16	3/16
-322	1.225	.012	.210	1-1/4	1-5/8	3/16
-323	1.287	.012	.210	1-5/16	1-11/16	3/16
-324	1.350	.012	.210	1-3/8	1-3/4	3/16
-325	1.475	.015	.210	1-1/2	1-7/8	3/16
-326	1.600	.015	.210	1-5/8	2	3/16
-327	1.725	.015	.210	1-3/4	2-1/8	3/16
-328	1.850	.015	.210	1-7/8	2-1/4	3/16
-329	1.975	.018	.210	2	2-3/8	3/16
-330	2.100	.018	.210	2-1/8	2-1/2	3/16
-331	2.225	.018	.210	2-1/4	2-5/8	3/16
-332	2.350	.018	.210	2-3/8	2-3/4	3/16
-333	2.475	.020	.210	2-1/2	2-7/8	3/16
-334	2.600	.020	.210	2-5/8	3	3/16
-335	2.725	.020	.210	2-3/4	3-1/8	3/16
-336	2.850	.020	.210	2-7/8	3-1/4	3/16
-337	2.975	.024	.210	3	3-3/8	3/16

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-338	3.100	.024	.210	3-1/8	3-1/2	3/16
-339	3.225	.024	.210	3-1/4	3-5/8	3/16
-340	3.350	.024	.210	3-3/8	3-3/4	3/16
-341	3.475	.024	.210	3-1/2	3-7/8	3/16
-342	3.600	.028	.210	3-5/8	4	3/16
-343	3.725	.028	.210	3-3/4	4-1/8	3/16
-344	3.850	.028	.210	3-7/8	4-1/4	3/16
-345	3.975	.028	.210	4	4-3/8	3/16
-346	4.100	.028	.210	4-1/8	4-1/2	3/16
-347	4.225	.030	.210	4-1/4	4-5/8	3/16
-348	4.350	.030	.210	4-3/8	4-3/4	3/16
-349	4.475	.030	.210	4-1/2	4-7/8	3/16
-350	4.600	.030	.210	4-5/8	5	3/16
-351	4.725	.030	.210	4-3/4	5-1/8	3/16
-352	4.850	.030	.210	4-7/8	5-1/4	3/16
-353	4.975	.037	.210	5	5-3/8	3/16
-354	5.100	.037	.210	5-1/8	5-1/2	3/16
-355	5.225	.037	.210	5-1/4	5-5/8	3/16
-356	5.350	.037	.210	5-3/8	5-3/4	3/16
-357	5.475	.037	.210	5-1/2	5-7/8	3/16
-358	5.600	.037	.210	5-5/8	6	3/16
-359	5.725	.037	.210	5-3/4	6-1/8	3/16
-360	5.850	.037	.210	5-7/8	6-1/4	3/16
-361	5.975	.037	.210	6	6-3/8	3/16
-362	6.225	.040	.210	6-1/4	6-5/8	3/16
-363	6.475	.040	.210	6-1/2	6-7/8	3/16
-364	6.725	.040	.210	6-3/4	7-1/8	3/16
-365	6.975	.040	.210	7	7-3/8	3/16
-366	7.225	.045	.210	7-1/4	7-5/8	3/16

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-367	7.475	.045	.210	7-1/2	7-7/8	3/16
-368	7.725	.045	.210	7-3/4	8-1/8	3/16
-369	7.975	.045	.210	8	8-3/8	3/16
-370	8.225	.050	.210	8-1/4	8-5/8	3/16
-371	8.475	.050	.210	8-1/2	8-7/8	3/16
-372	8.725	.050	.210	8-3/4	9-1/8	3/16
-373	8.975	.050	.210	9	9-3/8	3/16
-374	9.225	.055	.210	9-1/4	9-5/8	3/16
-375	9.475	.055	.210	9-1/2	9-7/8	3/16
-376	9.725	.055	.210	9-3/4	10-1/8	3/16
-377	9.975	.055	.210	10	10-3/8	3/16
-378	10.475	.060	.210	10-1/2	10-7/8	3/16
-379	10.975	.060	.210	11	11-3/8	3/16
-380	11.475	.065	.210	11-1/2	11-7/8	3/16
-381	11.975	.065	.210	12	12-3/8	3/16
-382	12.975	.065	.210	13	13-3/8	3/16
-383	13.975	.070	.210	14	14-3/8	3/16
-384	14.975	.070	.210	15	15-3/8	3/16
-385	15.955	.075	.210	16	16-3/8	3/16
-386	16.955	.080	.210	17	17-3/8	3/16
-387	17.955	.085	.210	18	18-3/8	3/16
-388	18.955	.090	.210	19	19-3/8	3/16
-389	19.955	.095	.210	20	20-3/8	3/16
-390	20.955	.095	.210	21	21-3/8	3/16
-391	21.955	.100	.210	22	22-3/8	3/16
-392	22.940	.105	.210	23	23-3/8	3/16
-393	23.940	.110	.210	24	24-3/8	3/16
-394	24.940	.115	.210	25	25-3/8	3/16
-395	25.940	.120	.210	26	26-3/8	3/16

We're your source for expertise in virtually every area, including materials, design, prototyping, testing and more. We'll work with you to set up a custom just-in-time delivery program. Our Electronic Data Interchange (EDI) reduces even more costs and time. We'll barcode all incoming and outgoing shipments for easy verification and to streamline your receiving process.

When it comes to serving you, we're as reliable as our O-Rings. For more information, quick quotations, expert consultation and responsive customer service call us at 800.553.5054, or visit our website at www.allsealsinc.com.

QUALITY | VALUE | SERVICE

CROSS SECTION .275" ± .006"

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-425	4.475	.033	.275	4-1/2	5	1/4
-426	4.600	.033	.275	4-5/8	5-1/8	1/4
-427	4.725	.033	.275	4-3/4	5-1/4	1/4
-428	4.850	.033	.275	4-7/8	5-3/8	1/4
-429	4.975	.037	.275	5	5-1/2	1/4
-430	5.100	.037	.275	5-1/8	5-5/8	1/4
-431	5.225	.037	.275	5-1/4	5-3/4	1/4
-432	5.350	.037	.275	5-3/8	5-7/8	1/4
-433	5.475	.037	.275	5-1/2	6	1/4
-434	5.600	.037	.275	5-5/8	6-1/8	1/4
-435	5.725	.037	.275	5-3/4	6-1/4	1/4
-436	5.850	.037	.275	5-7/8	6-3/8	1/4
-437	5.975	.037	.275	6	6-1/2	1/4
-438	6.225	.040	.275	6-1/4	6-3/4	1/4
-439	6.475	.040	.275	6-1/2	7	1/4
-440	6.725	.040	.275	6-3/4	7-1/4	1/4
-441	6.975	.040	.275	7	7-1/2	1/4

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-442	7.225	.045	.275	7-1/4	7-3/4	1/4
-443	7.475	.045	.275	7-1/2	8	1/4
-444	7.725	.045	.275	7-3/4	8-1/4	1/4
-445	7.975	.045	.275	8	8-1/2	1/4
-446	8.475	.055	.275	8-1/2	9	1/4
-447	8.975	.055	.275	9	9-1/2	1/4
-448	9.475	.055	.275	9-1/2	10	1/4
-449	9.975	.055	.275	10	10-1/2	1/4
-450	10.475	.060	.275	10-1/2	11	1/4
-451	10.975	.060	.275	11	11-1/2	1/4
-452	11.475	.060	.275	11-1/2	12	1/4
-453	11.975	.060	.275	12	12-1/2	1/4
-454	12.475	.060	.275	12-1/2	13	1/4
-455	12.975	.060	.275	13	13-1/2	1/4
-456	13.475	.070	.275	13-1/2	14	1/4
-457	13.975	.070	.275	14	14-1/2	1/4
-458	14.475	.070	.275	14-1/2	15	1/4

AS568	—Dimensions in Inches—			—Nominal Size—		
	I.D.	±	C/S	I.D.	O.D.	C/S
-459	14.975	.070	.275	15	15-1/2	1/4
-460	15.475	.070	.275	15-1/2	16	1/4
-461	15.955	.075	.275	16	16-1/2	1/4
-462	16.455	.075	.275	16-1/2	17	1/4
-463	16.955	.080	.275	17	17-1/2	1/4
-464	17.455	.085	.275	17-1/2	18	1/4
-465	17.955	.085	.275	18	18-1/2	1/4
-466	18.455	.085	.275	18-1/2	19	1/4
-467	18.955	.090	.275	19	19-1/2	1/4
-468	19.455	.090	.275	19-1/2	20	1/4
-469	19.955	.095	.275	20	20-1/2	1/4
-470	20.955	.095	.275	21	21-1/2	1/4
-471	21.955	.100	.275	22	22-1/2	1/4
-472	22.940	.105	.275	23	23-1/2	1/4
-473	23.940	.110	.275	24	24-1/2	1/4
-474	24.940	.115	.275	25	25-1/2	1/4
-475	25.940	.120	.275	26	26-1/2	1/4

O-RINGS FOR TUBE FITTING BOSSES

AS568	—Dimensions in Inches—				—Dimensions in Millimeters—				O-Ring Volume (cubic inches)	—Tube Size—	
	I.D.	±	C/S	±	I.D.	±	C/S	±		OD	Dash No.**
-901	.185	.005	.056	.003	4.70	0.13	1.42	0.08	0.0019	3/32	
-902	.239	.005	.064	.003	6.07	0.13	1.63	0.08	0.0031	1/8	2
-903	.301	.005	.064	.003	7.65	0.13	1.63	0.08	0.0037	3/16	3
-904	.351	.005	.072	.003	8.92	0.13	1.83	0.08	0.0054	1/4	4
-905	.414	.005	.072	.003	10.52	0.13	1.83	0.08	0.0062	5/16	5
-906	.468	.005	.078	.003	11.89	0.13	1.98	0.08	0.0082	3/8	6
-907	.530	.007	.082	.003	13.46	0.18	2.08	0.08	0.0102	7/16	7
-908	.644	.009	.087	.003	16.36	0.23	2.21	0.08	0.0137	1/2	8
-909	.706	.009	.097	.003	17.93	0.23	2.46	0.08	0.0186	9/16	9
-910	.755	.009	.097	.003	19.18	0.23	2.46	0.08	0.0198	5/8	10
-911	.863	.009	.116	.004	21.92	0.23	2.95	0.10	0.0326	11/16	11
-912	.924	.009	.116	.004	23.47	0.23	2.95	0.10	0.0345	3/4	12
-913	.986	.010	.116	.004	25.04	0.25	2.95	0.10	0.0366	13/16	13
-914	1.047	.010	.116	.004	26.59	0.25	2.95	0.10	0.0386	7/8	14
-916	1.171	.010	.116	.004	29.74	0.25	2.95	0.10	0.0427	1	16
-918	1.355	.012	.116	.004	34.42	0.30	2.95	0.10	0.0489	1-1/8	18
-920	1.475	.014	.118	.004	37.47	0.36	3.00	0.10	0.0547	1-1/4	20
-924	1.720	.014	.118	.004	43.69	0.36	3.00	0.10	0.0631	1-1/2	24
-928	2.090	.018	.118	.004	53.09	0.46	3.00	0.10	0.0759	1-3/4	28
-932	2.337	.018	.118	.004	59.36	0.46	3.00	0.10	0.0843	2	32

**The 900 series boss seals are designed to seal straight thread tube fittings when they are fastened into a boss. In this type of fitting the O-Ring is not located in a conventional rectangular groove. Rather, the seal is obtained when the gland components exert a diagonal squeeze through the O-Ring cross section.

O-RINGS



CALIFORNIA

20762 Linear Lane
Lake Forest, CA 92630
800.553.5054 TOLL FREE
714.556.4931 PHONE
714.557.3257 FAX

TEXAS

4407 Halik Road, Building A
Pearland, TX 77581
800.553.5054 TOLL FREE
281.404.4384 PHONE
281.715.5379 FAX

CONTACT

sales@allsealsinc.com

www.allsealsinc.com

© 2015, All Seals, Inc. Rev 8.17

WARRANTIES All Seals, Inc. warrants the products to be free of defects in materials and workmanship (as defined by the engineering print or standard industry specification) for a period of ninety (90) days. Should the product(s), in All Seals' opinion, malfunction during the warranty period, All Seals, Inc. will, at its option, repair or replace the defective product(s) at no charge provided that the product(s) have not been subjected to misuse, abuse, or non-All Seals-authorized alternations, modifications, or repairs. All Seals, Inc. provides only the warranties set forth herein. All other warranties, expressed or implied, including but not limited to the warranties of merchantability and fitness for a particular purpose, are excluded in the event the product(s) provided herein malfunction. Buyer's sole remedy shall be repair or replacement as provided above. Under no circumstances shall All Seals, Inc. be liable in any way to the buyer or user for any damages, including any lost profits or other indirect, special, incidental or consequential damages of any kind or nature, arising out of use of, or inability to use such product.