

Simplify Your Procurement - Optimize Your Engineering

2110 S. Yale Street Santa Ana, California 92704 Phone: (714) 556-4931 Toll Free: (800) 553-5054 Fax: (714) 557-3257 Email: asi@allsealsinc.com

www. allsealsinc.com













Master Distributor with Global Sources

anufacturers (Partial listing)
























































Materials (Wide variety of elastomer, plastic and metal materials)



- Standard, Exotic and Custom blends that can control Hardness (Durometer), Conductivity, Friction, Temperature, Gas Permeability, Chemical Compatibility, Curing Agents, Abrasion and Tear Resistance, Oil/ Ozone/ pH/ Water and Weather resistance.
- Nitrile (Buna N, Buna S), Butyl, Fluorocarbon, (Viton® –A, B, GF, GFLT),
 PerFluoroelastomer (Chemraz ®, Simriz ®, Kalrez®), Tetrafluoroethylene (Aflas®),
 PTFE (Teflon®), Silicone, FluoroSilicone, Ethylene Propylene (EPDM), Chloroprene
 (Neoprene®), Polyurethane, Natural, Hydrogenated Nitrile (HNBR), Polyacrylate.
- Foam, Sponge, Cork, Leather, Mylar, Kapton, Fibre, Felt, EAR, PSA backing.
- Plastic injection molded parts made from a variety of materials.
- Stamped or Machined metal parts made from Carbon, Tool or Stainless steels, and Aluminum.





























Products



O-RINGS DUAD RINGS BACK UP RINGS

- Lathe Cuts
- Custom O-Rings
- Disogrin O-Rings
- Metric Sizes
- Miniature Sizes
- Non-Standard Sizes
- Teflon®/ Teflon® coated
- Teflon® Encapsulated
 Spliced and Special O-ring
- Military
- Quad Ŕings
- O-Ring Kits
- O-Ring Splicing Kits
- Retaining Rings



CUSTOM DIAPHRAGM

- Custom materials
- Impregnated elastomers



CUSTOM **GASKETS**

- Precision Die Stamping from both Steel Rule and Class A tooling
- Spiral Wound
- Sheet stock
- Spring washer



RUBBER **PRODUCTS**

- Bumpers/Grommets
- Cord Stock
- Custom Molded
- Custom Extruded
- Dampening Materials
- Molded Foam Products
- Metal-To-Rubber Bonded
- Fastener/Fitting Seals
- Molding
- Sheet Stock
- Tubina
- Vibration Mounts
- Ground Rubber Balls
- Bumpons
- Caplugs



MECHANICAL SEALS

- Pump Repair Kits
- Cartridge and Bellow Type
- Inside-Outside-Shaft Mounted
- Single-Double-Tandem
- Metric
- Carbon
- Ceramic
- Ni-Resist
- Cast Iron
- 18-8 (302/4), 316 SS
- Silicon Carbide
- Tungsten Carbide Hastalloy
- Monel
- Springs
- Sleeve
- Installation lubricant
- Abrasive Separators



HYDRAULIC SEALS

- V-Cup
- U-Cup
- Piston
- Metric
- Spring Loaded U-Cup



TEFLON PRODUCTS

- For Aerospace and
- Industrial Application
- For Low Friction
- Spring Loaded Styles
- Slipper Seals
- Plus Seals & Cap Seals
- Channel Seals
- Step Seals
- Glyd Rings
- Backup Řings
- Piston Seals



OTHER PRODUCTS

- Dispensing Equipment
- **Measuring Devices**



SEALS

- Inch
- Metric
- Spring and Non-Spring loaded
- High pressure
- PTFE
- · Viton and all other materials



LUBRICANTS

- 221R Silicone Grease
- Coolube 65, Hydrolube
- HUSKEY™ Specialty Lubricants
- HVS-100 Silicone Grease
- Molykote Industrial Lubricants
- Thread Sealant
- PTFE Tape



PACKING

- Braided Packing
- Spring Energized • Chevron V packing
- W packing
- U Ċups
- Piston Rings
- Polyseals
- Spliced and special O-rings
- Metric
- Polypaks
- V packing T seals
- Wipers



PLASTIC INJECTION **MOLDED PARTS**

- Custom shapes
- Wide variety of plastic and rubber materials
- Over-molded parts
- Extruded parts



METAL PARTS

- Machined
- Stamped
- Cast
- Electro polished
- Etched
- Carbon, stainless, & tool steels
- Copper alloys
- Iron alloys Wave Washers
- Retaining Ring



ADHESIVES

- Joint Sealant
- Anaerobic Cvanoacrvlate
- Cyberbond
- Epoxies Silicone RTV
- Urethane, Acrylic UV Curing Adhesives and
- Equipment Thread Sealant
- PTFE Tape



PERMAGLYDE

Friction can be an asset at times, but in general it is a problem for most sealing applications. The heat and physical damage caused by Friction and torque can drastically reduce the effectiveness and lifetime of a seal. The patented PermaGlyde® process retains all of core elastomer physical properties while subjecting the surface to a Fluorination process. This process drastically reduces the stiction by chemically changing the rubber so that the physical properties are permanently upgraded to reduce breakaway friction, increase lubricity and decrease adhesion. Our testing has shown this is equivalent to the Polymod ® process.



Value Added Services

Engineering Assistance



Design Consultation



Material Compatibility



Value/Reverse Engineering



Friction Management

Purchasing Assistance



Vendor Consolidation



Equivalent Materials



Vendor Managed Inventory



Cost Reduction



Global Sourcing

o perations Assistance



Kitting



Sub Assembly



Specialty Packaging



Material Traceability



Certifications



PPAP Approvals



Bin Stocking



Shipment Consolidation





2110 S. Yale Street Santa Ana, California 92704 Phone: (714) 556-4931 Toll Free: (800) 553-5054 Fax: (714) 557-3257 Email: asi@allsealsinc.com